

HiKOKI Nederland

www.hikoki-powertools.nl

Follow us on our socials and never miss out on HiKOKI news.

hikoki-powertools.nl



36V and 18V Cordless Circular Saws C3606DUM / C1806DUM



Precision in every single cut.

Discover our new C3606DUM and C1806DUM circular saws, embodying cutting-edge precision with Innovative Deep Cut Technology and guide rail compatibility.



C3606DUM / C1806DUM

Cordless Circular Saws

| Specifications | C3606DUM | C1806DUM | Versions ² | |
|----------------------------------|--------------------|--------------------|-----------------------|---|
| Voltage | 36V | 18V | KSC3606DUMWP1Z | 2x battery BSL36A18X, fastcharger |
| No-load speed | 5,600 rpm | 4,500 rpm | | UC18YSL3, saw blade wood 165 mm, |
| Saw blade diameter | 165 mm | 165 mm | | hex bar wrench, rip fence, stackable case |
| Mount hole diameter | 20 mm | 20 mm | | HSC IV, 160 cm guide rail, cardboard box |
| Max. cutting depth 90° | 66 mm | 66 mm | C3606DUMWPZ: | 2x battery BSL36A18X, fastcharger |
| Max. cutting depth 45° | 43 mm | 43 mm | | UC18YSL3, saw blade wood 165 mm, |
| Max. cutting depth 90° | 61 mm | 61 mm | | hex bar wrench, rip fence, stackable |
| on guide rail | | | | case HSC IV |
| Bevel capacity | 0° - 45° | 0° - 45° | KSC3606DUMWP1Z | Saw blade wood 165 mm, hex bar |
| Brushless motor | \checkmark | \checkmark | | wrench, rip fence, stackable case HSC IV, |
| Motor modes | 3 (silent, | 2 | | 160 cm guide rail, cardboard box |
| | medium, high) | (silent, high) | C3606DUMW2Z: | Saw blade wood 165 mm, hex bar |
| Guide rail compatibility | ✓ | ✓ | | wrench, rip fence, stackable case HSC IV |
| Deep Cut Technology | \checkmark | \checkmark | | |
| Brake | \checkmark | \checkmark | KSC1806DUMWP1Z | 2x battery BSL1850MA, fastcharger |
| LED light | \checkmark | \checkmark | | UC18YSL3, saw blade wood 165 mm, |
| Soft start | \checkmark | \checkmark | | hex bar wrench, rip fence, stackable case |
| Constant speed control | \checkmark | \checkmark | | HSC IV, 160 cm guide rail, cardboard box |
| Kickback protection | \checkmark | \checkmark | C1806DUMWPZ: | 2x battery BSL1850MA, fastcharger |
| Vacuum cleaner port | \checkmark | \checkmark | | UC18YSL3, saw blade wood 165 mm, |
| Dimensions (L x W x H) | 314 x 198 x 263 mm | 314 x 198 x 263 mm | | hex bar wrench, rip fence, stackable |
| Weight with battery ¹ | 4.1 kg | 3.9 kg | | case HSC IV |
| - | - | - | KSC1806DUMW21Z | : Saw blade wood 165 mm, hex bar |
| | | | | wrench, rip fence, stackable case HSC IV, |
| | | | | 160 cm guide rail, cardboard box |

C1806DUMW2Z:

C1806DUMW4Z:

Saw blade wood 165 mm, hex bar

Saw blade wood 165 mm, hex bar

wrench, rip fence, cardboard box

wrench, rip fence, stackable case HSC IV

Always a perfect finish.



Three* speed modes for the best results:

- Fast and powerful cuts
- Medium: Smooth finishing with constant speed
- Silent: Highest control and low noise

| Mode | High Medium | | Silent |
|---------------------------|--------------|-------------|-------------|
| Status of indicator lamp | MODE - 2 1 1 | MODE 2 1 | MODE 2 1 |
| No-load speed C3606DUM | 5,600 /min. | 4,300 /min. | 2,000 /min. |
| No-load speed C1806DUM | 4,300 /min. | - | 2,000 /min. |


^{*}Applies to C3606DUM. C1806DUM has two speed modes.

Expand your circular saw with our guide rails GR800 or GR1600.

Explore a variety of accessories to boost your precision.

| Description | Art.no. |
|-----------------------------------|---------|
| Guide rail GR800 | 4100071 |
| Guide rail GR1600 | 4100072 |
| Carrier bag for guide rail GR1600 | 379259 |
| Connector for guide rail | 4100080 |
| Miter fence | 379264 |
| Steel screw clamp | 711237 |
| Steel lever clamp | 711238 |





Dust-free at a turn and pull.

The rotatable and lockable dust ejection nozzle assures high flexibility and a dust-free jobsite.

Built-in safety for every project.

Our C3607DB's fast-stopping brake and proactive kick-back protection ensure seamless safety and enduring precision, boosting your success with reliable and controlled cuts.

¹ Weight according to EPTA-2004 procedure. ² Standard accessories vary by country or area.