

HiKOKI Nederland

www:hikoki-powertools.nl

Follow us on our socials and never miss out on HiKOKI news.

hikoki-powertools.nl







36V Cordless Circular Saw C3607DB

Torque and speed on demand. **Discover our new Cordless Circular Saw** with Torque Boost technology. C3607DB **Cutting depth of 64.5 mm** Torque Boost motor technology Guide rail adapter included Big rafter hook HIKOKI BRUSHLESS

Adaptive cutting power.

We introduce 36V brushless circular saw C3607DB, which combines power and precision. Its robust aluminum die-cast base ensures stability and provides precise measurements.



C3607DB

Cordless Circular Saw

_				
- 5	nec	'ITIC	atic	ns
_	~~			

Voltage 4,500 - 6,000 /min. No-load speed Saw blade diameter 190 mm Mount hole diameter 30 mm Maximum cutting depth 90° 64.5 mm Maximum cutting depth 45° 49 mm Bevel capacity 45°/0° Brushless motor Guide rail compatibility Rafter hook Brake LED Soft start Constant speed control Kickback protection Dimensions (L x W x H) 313 x 221 x 280 mm Weight with BSL36A18X²

/ersions³

KSC3607DBWR1Z: 2x BSL36A18X battery, fastcharger UC18YSL3, guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key,

stackable case HSC IV, 160 cm guide rail, carton

C3607DBWRZ: 2x BSL36A18X battery, fastcharger UC18YSL3, guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key,

stackable case HSC IV

KSC3607DBW21Z: Guide rail adapter, rafter hook, dust adapter, saw blade wood, hex key, stackable case HSC IV, 160 cm guide rail, carton

C3607DBW2Z: Guide rail adapter, rafter hook, dust adapter, saw blade wood,

hex key, stackable case HSC IV



Built-in safety for every project.

Our C3607DB's fast-stopping brake and proactive kick-back protection ensure seamless safety.




Dynamic power, effortless cutting.

The Torque Boost motor has two preselectable modes: Auto switch mode and High torque mode. In the Auto switch mode, when the electronics detect changes in the workpiece structure, it automatically switches between highest blade speed and High torque to guarantee highly efficient and fast cuts.

Torque boost motor settings.

Mode	Auto switch	High torque	
Status of indicator lamp	0		
No-load speed	6,000 /min.	4,500 /min.	



Benefits of Torque Boost Technology

Increased cutting speed compared to predecessor in auto switch mode.

C3607DB

200%

C3607DA

100%

Extended runtime cutting 50x100 mm soft wood in high torque mode.

C3607DB Auto switch

420 cuts

C3607DB High torque

770 cuts

n combination with BSL36A18



Guide rail adapter compatible with HiKOKI, Makita, Milwaukee, Festool, Metabo, and Hilti.



Dust adapter for use with vacuum cleaners for a clean workspace.



Big rafter hook for convenient storage on the jobsite.

High quality accessories for your circular saw.

Description	Art.no.
Guide rail GR800	4100071
Guide rail GR1600	4100072
Carrier bag for guide rails	379259
Connector for guide rail	4100080
Miter fence	379264
Steel screw clamp	711237
Steel lever clamp	711238